

- Protects appliances and fixtures from staining
- Safe - No Chemicals
- Low cost - Requires only periodic backwashing
- No Filters to change
- Long material life expectancy
- High iron removal efficiency
- Reduces hydrogen sulfide (rotten egg odor)*

* Use Guardian Carbon or Guardian O₂/Carbon for this application



****PUMP OUTPUT MUST MATCH OR EXCEED BACKWASH RATE**

	Tank Size (inches)	Media (cu.ft.)	Media Type	Backwash Flow Rate (gpm)	Service Flow Rate (gpm)
Guardian Pro	13 x 52	2.5	Clinoptilolite	10.0	4.6
Guardian Pro O ₂	13 x 52	2.5	O ₂ Catalytic	7.5	4.6
Guardian Pro Carbon	13 x 52	2.5	Cat Carbon	7.5	4.6
Guardian Pro O ₂ /Carbon	13 x 52	2.5	O ₂ Cat/Carbon	7.5	4.6

**Guardian Pro Series not to be used with microbiologically unsafe water sources

**Free chlorine concentration less than 0.5ppm and PH range of 6.8-9.0 is required for Guardian Pro O₂ and Guardian O₂/Carbon systems

**Guardian Pro Series available in 1.25", 1.5", and 2" systems

SOLD BY: